

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,266,354 B2
APPLICATION NO. : 09/888795
DATED : September 4, 2007
INVENTOR(S) : Jian et al.

Page 1 of 3

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

The title page showing the illustrative figure should be deleted to be replaced with the attached title page.

The drawing sheet, consisting of Fig. 4, should be deleted to be replaced with the drawing sheet, consisting of Fig. 4, as shown on the attached pages.


In Column 7, Line 42, delete "6½%" and insert -- 6½ --, therefor.

In Column 9, Line 23, in Claim 10, before "sample" delete "the" and insert -- a --, therefor.

In Column 12, Line 13, in Claim 32, delete "(COMA)" and insert -- (CDMA) --, therefor.

Signed and Sealed this

Eighteenth Day of May, 2010

A handwritten signature in black ink that reads "David J. Kappos". The signature is written in a cursive, flowing style with a large, stylized 'D' and 'K'.

David J. Kappos
Director of the United States Patent and Trademark Office

(12) **United States Patent**
Jian et al.

(10) **Patent No.:** **US 7,266,354 B2**
(45) **Date of Patent:** **Sep. 4, 2007**

(54) **REDUCING THE PEAK-TO-AVERAGE POWER RATIO OF A COMMUNICATION SIGNAL**

(75) **Inventors:** **Heng-Yu Jian, Los Angeles, CA (US);**
Lennart Mathe, San Diego, CA (US)

(73) **Assignee:** **Telefonaktiebolaget LM Ericsson**
(publ) (SE)

(*) **Notice:** Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1451 days.

(21) **Appl. No.:** **09/888,795**

(22) **Filed:** **Jun. 25, 2001**

(65) **Prior Publication Data**
US 2002/0197970 A1 Dec. 26, 2002

(51) **Int. Cl.**
H04B 1/06 (2006.01)

(52) **U.S. Cl.** 455/245.2; 455/251.1;
455/245.1

(58) **Field of Classification Search** 455/67.13,
455/556.1, 114.3, 144, 194.2, 211, 245.1,
455/245.2, 251.1, 256; 375/396; 342/373;
327/356

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,302,914 A * 4/1994 Arntz et al. 330/129

5,638,403 A 6/1997 Birchler et al.
5,710,990 A * 1/1998 Long et al. 455/103
5,727,026 A * 3/1998 Beukema 375/296
6,504,862 B1 * 1/2003 Yang 375/146
6,687,511 B2 * 2/2004 McGowan et al. 455/522
2001/0006359 A1 * 7/2001 Suzuki et al. 333/14
2003/0198299 A1 * 10/2003 Redfern 375/260

FOREIGN PATENT DOCUMENTS

DE 19548172 5/1996
EP 0977355 2/2000
WO WO 0054426 9/2000

* cited by examiner

Primary Examiner—Matthew Anderson

Assistant Examiner—Tan Trinh

(74) *Attorney, Agent, or Firm*—Coats & Bennett, P.L.L.C.

(57) **ABSTRACT**

Systems and methods are provided for reducing the peak to average ratio of signals, so that the signals can be amplified more efficiently. An error signal that corresponds to crests of the input signal is generated, and subtracted from the input signal. When a crest is so long that it corresponds to more than one sample, only the maximum sample contained in the crest is used to form the error signal. Optionally, multiple stages of decresting may be implemented sequentially.

36 Claims, 9 Drawing Sheets




Figure 4

